

## FEATURES

- 30 micron filter bag is the supplied as standard accessory.
- 5-micron filter bag for optional accessory.
- The plastic bag can use for bottom collecting bag in order to replacing clothes bag.



UB-207D



UB-207HD



UB-402H

Also Available



CK-600T

Canister filter for 4 HP~10 HP dust collector.

Also Available



CK-600TH

HEPA canister filter for 4HP~10HP dust collector.

## FEATURES

- Canister filters always resist more hazardous fine dust before it can become airborne or enter your lungs.
- Manual cleaning system can easily help to clean the canister filter.
- Cartridge filter is made of spun-bond polyester that filters 99.9% of particles from 0.2 to 2 microns in size.
- The inner frame provides the ability to use convenient plastic bags inside your drum.



UB-1000V  
(MOVEABLE TYPE)



UB-2000V  
(MOVEABLE TYPE)  
(Exclusive in North America)



UB-3000V  
(MOVEABLE TYPE)  
(Exclusive in North America)



MODEL: IF-380 (For 1 HP use)



INNER FRAME  
(PE BAG HOLDER)

- Make dust disposal quick and easy.
- Heavy-duty bags simply lift out of the drum; therefore there is no mess dumping.



QUICK LIFT LEVER

- Quick and smart device for pulling out the steel drum which one person can be done easily.

SPECIFICATIONS	UB-207D		UB-207HD		UB-402H	
Motor	7-1/2 HP / 60 HZ	5.6 KW / 50 HZ	7-1/2 HP / 60 HZ	5.6 KW / 50 HZ	10 HP / 60 HZ	7.5 KW / 50 HZ
Impeller Size	16"	406 mm	16"	406 mm	17"	432 mm
Air Suction W/O Bag	4660 CFM	6334 m <sup>3</sup> /h	4700 CFM	6200 m <sup>3</sup> /h	5500 CFM	7300 m <sup>3</sup> /h
Max. Static Pressure	15.6 InH <sub>2</sub> O	396 mmAq	16.3 InH <sub>2</sub> O	414 mmAq	17.6 InH <sub>2</sub> O	447 mmAq
Inlet Diameter	9" x 4" x 5	229 x 102 mm x 5	9" x 4" x 5	229 x 102 mm x 5	9" x 4" x 5	229 x 102 mm x 5
Bag Diameter	23-5/8"	600 mm	23-5/8"	600 mm	23-5/8"	600 mm
Bag Height	70-3/4"	1800 mm	70-3/4"	1800 mm	70-3/4"	1800 mm
Noise Rate (@3M)	90 dB		95 dB		98 dB	
Overall Size (L x W x H)	1980 x 700 x 3680 mm		3000 x 690 x 3610 mm		1700 x 1700 x 2530 mm	
Packing Size (L x W x H)	1500 x 780 x 760 mm		1750 x 770 x 745 mm		1340 x 1150 x 775 mm	
N.W. / G.W. / Cuft	141 kgs / 163 kgs / 31.4'		190 kgs / 250 kgs / 35.5'		187 kgs / 230 kgs / 42'	

\* Chang tjer reserves the right to change or modify specs and system appearance without notice. Actual system appearance may vary.

SPECIFICATIONS	UB-1000V	UB-2000V	UB-3000V	
Motor	1 HP / 0.75 KW	2 HP / 1.5 KW	3 HP / 60 HZ	2.25 KW / 50 HZ
Air Suction W/O Bag	604 CFM / 785 m <sup>3</sup> /h	1450 CFM / 1880 m <sup>3</sup> /h	2111 CFM	2850 m <sup>3</sup> /h
Max. Static Pressure	7 InH <sub>2</sub> O / 178 mmAq	10.5 InH <sub>2</sub> O / 266 mmAq	11.2 InH <sub>2</sub> O	285 mmAq
Inlet Diameter	6" x 4" x 2	6" x 4" x 2	8" x 4" x 3	
Drum Capacity	20 gallons	28 gallons	63 gallons	
Noise Rate (@3M)	75 dB	76 dB	82 dB	
Filter Surface	3.75 M <sup>2</sup>	3.75 M <sup>2</sup>	6.25 M <sup>2</sup>	
Overall Size (L x W x H)	1000 x 500 x 1600 mm	1200 x 700 x 1800 mm	1200 x 850 x 2200 mm	
Packing Size (L x W x H)	1050 x 560 x 780 mm	1140 x 675 x 940 mm	Machine: 1390 x 765 x 960 mm Stand: 1230 x 445 x 435 mm	
N.W. / G.W. / Cuft	55 kgs / 62.5 kgs / 16.2'	93 kgs / 106 kgs / 25.5'	Machine: 100 kgs / 125 kgs / 36' Stand: 10 kgs / 15 kgs / 8.4'	

\* Chang tjer reserves the right to change or modify specs and system appearance without notice. Actual system appearance may vary.