

6" x 108" OSCILLATING EDGE BELT SANDER

FEATURES

- Easy to operate oscillating belt sander.
- Tables move up and down to suit the job.
- Front table tilts 45° for beveled edge sanding.
- Easy adjustment of abrasive belt tension and tracking.
- Graphite backing reduces friction for longer belt life.
- Precision machined, dynamically balanced aluminum drive pulleys.
- Heavy steel base ensures a solid stable platform while sanding.
- Large steel front table equipped with tilt and height adjustments.



OS-610
(SINGLE ALUMINUM TABLE)

SPECIFICATIONS		OS-610
Motor	2 HP / 220V / 60 HZ	
Belt Size	152 x 2743 mm	
Belt Speed	3224 FPM (60 HZ) 829 MPM (50 HZ)	
Front Table Size (L x W)	920 x 300 mm	
Table Tilt	45°	
Table Height	810 mm	
Dust Port	4" (100 mm) x 2	
Overall Size (L x W x H)	1620 x 660 x 1050 mm	
Packing Size (L x W x H)	1635 x 720 x 1230 mm	
N.W. / G.W. / Cuft	220 kgs / 245 kgs / 48'	

* Chang tjer reserves the right to change or modify specs and system appearance without notice. Actual system appearance may vary.




OS-610H
(SINGLE ALUMINUM TABLE)

SPECIFICATIONS		OS-610H
Motor	2 HP / 220V / 60 HZ	
Belt Size	152 x 2743 mm	
Belt Speed	3224 FPM (60 HZ) 829 MPM (50 HZ)	
Front Table Size (L x W)	920 x 300 mm	
Table Tilt	45°	
Table Height	810 mm	
Dust Port	4" (100 mm) x 2	
Overall Size (L x W x H)	1620 x 660 x 1050 mm	
Packing Size (L x W x H)	1635 x 720 x 1230 mm	
N.W. / G.W. / Cuft	220 kgs / 245 kgs / 48'	

* Chang tjer reserves the right to change or modify specs and system appearance without notice. Actual system appearance may vary.



• Dust hood



• Curved sanding



• Back side

9" x 138½" OSCILLATING EDGE BELT SANDER

FEATURES

- With its powerful 3HP motor can delivers the performance professional demand.
- Coupled with an industrial quality eccentric oscillation mechanism that delivers more efficient sanding, less tendency to burn and less belt loading.
- Heavy duty spring system allows easy adjustment for the front aluminum table for full use of the abrasive surface.
- Aluminum auxiliary contour table allow use of 4" idler roller as a drum sander.
- 9" Dia. Drive drum, 4" Dia. Idler drum.
- 9"-1/2" x 48" cast iron platen with graphite pad.
- Rugged bearing -assisted belt tension devise.
- Aluminum table travels 8" and tilts -5 to 45 degree.
- Dual 4" dust ports. Belt speed: 4200FPM.
- Sanding belt oscillate distance: 1/4" (6 mm)



OS-120E
(SINGLE ALUMINUM TABLE)



OS-912
(SINGLE ALUMINUM TABLE)




OS-120ED
(DOUBLE ALUMINUM TABLE)

SPECIFICATIONS		OS-120E
Motor	3 HP / 60 HZ / 220V / 3 PH	
Belt Size	230 x 3520 mm	
Front Table Size (L x W)	1210 x 300 mm	
Table Tilt	45°	
Table Height	830 mm	
Dust Port	4" (100 mm) x 2	
Overall Size (L x W x H)	2100 x 620 x 1020 mm	
Packing Size (L x W x H)	1980 x 605 x 1100 mm	
N.W. / G.W. / Cuft	295 kgs / 330 kgs / 47.5'	

* Chang tjer reserves the right to change or modify specs and system appearance without notice. Actual system appearance may vary.



• Dust hood




• Curved sanding

SPECIFICATIONS		OS-912
Motor	3 HP / 60 HZ / 220V / 3 PH	
Belt Size	230 x 3520 mm	
Front Table Size (L x W)	1210 x 300 mm	
Table Tilt	45°	
Table Height	830 mm	
Dust Port	4" (100 mm) x 2	
Overall Size (L x W x H)	2180 x 760 x 1250 mm	
Packing Size (L x W x H)	2000 x 760 x 1200 mm	
N.W. / G.W. / Cuft	279 kgs / 320 kgs / 64.5'	

* Chang tjer reserves the right to change or modify specs and system appearance without notice. Actual system appearance may vary.

SIDE VIEW

- Two sides working tables.



SPECIFICATIONS		OS-120ED
Motor	5 HP / 220V / 3 PH / 60 HZ	
Belt Size	230 x 3520 mm	
Working Capacity (L x W)	1212 x 300 mm	
Dust Port	4" (100 mm) x 2	
Overall Size (L x W x H)	2150 x 850 x 1020 mm	
Packing Size (L x W x H)	1975 x 950 x 1170 mm	
N.W. / G.W. / Cuft	380 kgs / 450 kgs / 78'	

* Chang tjer reserves the right to change or modify specs and system appearance without notice. Actual system appearance may vary.